

MARKET LEADER

- This versatile product is suitable for most entrance control.
- Boomgate Systems offer a wide range of options to compliment any prestige installation.
- Exported worldwide.





APPLICATIONS:

- To control high volumes at medium risk areas.
- Most suitable: office receptions, colleges and health clubs.
- Suitable for interior installations.



CONFIGURATIONS:

- Euro Style & Square.
- Mild Steel Powder Coated.
- Stainless 304 or 316.
- Granite for tops for square only.



SECURITY LEVEL RATING: (LOW / MEDIUM / HIGH / ULTRA SECURE)

| TYPE | DROP ARM | LOW | MEDIUM | HIGH | ULTRA SECURE |
|--------|----------|-----|--------|------|--------------|
| EURO | STYLE | Х | | | |
| SQUARE | STYLE | Х | | | |

DEFINITION

- **Security rating** is based on when the Drop Arm Barrier is in the locked position.
- Level of security is based on entry through the Drop Arm Barrier without unlocking the Drop Arm Barrier or use of access control.





TECHNICAL SPECIFICATION:

ELECTRICAL REQUIREMENTS:

Power: 220V AC ± 5%

Frequency: 50Hz


Power Consumption: 80W

Drop Arm Dimensions: See drawings on overleaf

Drop arms: 38mm Round Tube fixed arms

Weight: Euro Style 65kg and Square Shape is 50kg

Package size: Euro Style



SPECIAL FEATURES TO THE DROP ARM PEDESTRIAN BARRIER

- Designed for long-lasting reliability.
- Modular 11 pin programmable logic with LED indicators.
- Control panel comes standard with 12V output.
- Maintenance free mechanism.
- Factory tested recorded serial numbers.
- Manufacturers warranty
 - o 2 year mechanical warranty
 - o 1 year electrical warranty
- Zinc plated mechanism for corrosive protection.





ELECTRONICALLY CONTROLLED IN BOTH DIRECTIONS.

Power Locking Options: Fail safe unlock on power failure.

Fire Evacuation Option: If input trigger is latched, the drop arm will lower and

stay open until the trigger is removed.

Indication LED: The drop arm can be fitted with red/green walking

man to indicate go or stop.

Accessories available on request:

Push buttons, coin acceptors for paid access control, random search selectors.

Material options: Mild steel powder coated with textured exterior UV

resistant powder.

Granite top cover available on request for Square Drop Arm.

304 stainless steel brushed.

316 stainless steel brushed for extreme conditions.

Standard colours for M/S powder coated are Black.

Drop Arm comes standard with 38mm diameter S/S.

304 tube with clear polycarbonate skirt.

Drop Arm can be customised to customers request.



TECHNOLOGY:

- Locally manufactured 100% duty cycle gear torque motor.
- Ultra long lasting double buffer system in all models.
- Plug in microprocessor control logic.
- Safety sensor available in two options:
 - o Reflective type

o Non reflective type

SYSTEM COMPATIBILITY:

Boomgate Systems drop arm barriers are compatible with any access control system, time and attendance system or ticketing system. Only requires a n/o voltage free input trigger set for half a second.





GENIUS® PEDESTRIAN DROP ARM BARRIER



SQUARE DROP ARM BARRIER

EURO STYLE DROP ARM BARRIER





| 1 | Removable Lid | 5 | Cable entry |
|---|-------------------------------------|---|--|
| 2 | Lockable and removable door | 6 | Floor fixing position 4 x M12 Rawl bolts |
| 3 | Reader mounting position | 7 | Motor drive |
| 4 | 38mm Round tube stainless steel arm | 8 | Polycarbonate skirt |








GENIUS® PEDESTRIAN DROP ARM BARRIER




SQUARE DROP ARM BARRIER








EURO STYLE DROP ARM BARRIER





| SQUARE DROP ARM BARRIER | | | EURO STYLE DROP ARM BARRIER | | | |
|-------------------------|-----------------|---------------|-----------------------------|-----------------|--------|--|
| Α | Total Width | 1070mm | Α | Total Width | 1152mm | |
| В | Housing Depth | 332mm | В | Housing Depth | 385mm | |
| С | Drop Arm Length | <i>7</i> 38mm | С | Drop Arm Length | 767mm | |
| D | Drop Arm Height | 856mm | D | Drop Arm Height | 856mm | |
| Е | Overall Height | 1059mm | Е | Overall Height | 1150mm | |
| F | Overall Width | 332mm | F | Overall Width | 613mm | |

Due to continuous improvement, products and design are subject to change without notice.









18 Minerva Avenue, Leaglen, Florida, Roodepoort, SOUTH AFRICA

CAPE TOWN BRANCH: Tel: +27 21 551 0849 • Fax: +27 21 551 8627 • Email: salesct2@boomgatesystems.co.za

Unit 2 Crest Park, 12B Longclaw Drive, Montague Gardens, Cape Town, SOUTH AFRICA

www.boomgatesystems.co.za

- Manufacturers & Suppliers of:

 Traffic Barriers High Security Spike Barriers Road Blockers Turnstiles Security Booths Pedestrian Barriers

 Paraplegic Gates Speed Gates Bollards Goosenecks Magnetic Locks Metal Enclosures Rubber Islands